

The Next Generation Slab®



* Final survey will determine average depth required



SUPERCAP
The Next Generation Slab®



LATICRETE MIDDLE EAST LLC.
P.O. Box. 86028, Ras Al Khaimah - UAE
Tel. +971 7244 6396, +971 7244 5119.
Fax. +971 7244 5915.
www.laticrete.me | enquiry@laticrete.me

LATICRETE SUPERCAP, LLC
One LATICRETE Park North
Bethany, CT 06524-3423 USA
1.866.704.2247
+1.203.393.0010

www.laticretesupercap.com

SCT-0017-0115
©2015 LATICRETE SUPERCAP, LLC
All trademarks shown are the intellectual properties of their respective owners.



SUPERCAP
The Next Generation Slab®



Scan for more information.

The LATICRETE® SUPERCAP® System



Perfectly Flat, Dry Floors Delivered Faster, Safer, Greener

The LATICRETE® SUPERCAP® System combines our industry leading patented pump truck technology and innovative products to deliver perfectly flat, dry floors.

Time Tested. World Proven.

For over a decade we have delivered spectacular time-saving, cost-effective solutions that correct uneven concrete, reduce moisture vapor emissions and shorten build times. This system benefits the entire project from design to completion, all backed by the industry leader in globally proven construction solutions.



There's nothing like it in the industry!

LATICRETE® SUPERCAP® System Benefits

Underlayments/Overlays

- Quick drying – walkable in 2-4 hours, trades can work the next day
- High compressive strengths
- 4,000 and 5,000 + PSI formulas
- Lightweight formula option
- Low shrinkage, dimensionally stable
- Low alkali formula creates alkalinity buffer
- Inorganic formula will not contribute to mold/mildew
- UL GREENGUARD Gold certified

Moisture Vapor Control

- 100% solids epoxy
- Single coat application
- Exceeds ASTM F3010
- UL GREENGUARD Gold certified

Patented Pump Truck Technology

- Computer controlled mobile blending unit
- Dual-silo design enables on-site product blending
- Blending is done at street level, no unmixed material enters the building. No Silica dust.
- Industry leading volume, blend up to 30,000 lbs per hour
- Pump material up to 50 stories above ground
- On-board electric generator
- Long arm articulating crane
- Water supply system

The LATICRETE® SUPERCAP® System

- The superior choice for new construction or renovations
- Eliminates the need for power trowel finishing and curing compounds
- Can be applied over new concrete as early as 7 days with RH levels up to 100% as per ASTM F2170
- Guaranteed to meet substrate tolerances for all types of floor coverings
- Reduces MVER** to protect sensitive floor coverings
- Reduces build times and carrying costs
- Contributes towards USGBC LEED points
- Industry leading warranties
- Single source solution



* Refer to www.laticretesupercap.com for the latest Technical Data Sheets and installation guidelines
** Reduces Moisture Vapor Emission Rate with use of LATICRETE® SUPERCAP® Moisture Vapor Control